

Intrinsically Safe Dual-Function Headlamps

XPP-5450G

60/40 Lumens
 Spotlight

Spot High



Spot Low



XPP-5452G

115/65 Lumens
 Spotlight

Spot High




Spot Low



These non-rechargeable dual-function headlamps are cETLus, ATEX and IECEx listed Intrinsically Safe and PESO Approved. The headlamps each feature a multi-position tilt head design and include an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat. The top mounted switch provides user selectable high or low brightness spotlight operation. Power comes from 3 AAA premium batteries (included).

INTRINSICALLY SAFE



- cETLus, ATEX and IECEx listed Intrinsically Safe
- PESO Approval No : A/P/HQ/DL/104/5544 (P409850)
- High/low-brightness spotlight
- 80/92 Meter beam distance
- Engineered polymer housing

XPP-5450G
 XPP-5452G



XPP 5450 series

Intrinsically Safe Dual-Function Headlamps

XPP-5450G

XPP-5452G



XPP-5450G SPECIFICATIONS

- Lumens: high spotlight-60, low spotlight-40
- Run-time: high spotlight-13.5 hrs, low spotlight-22.75 hrs
- Beam distance: 80 meters
- Water / Dust rating: IP67
- Drop rating: 2 meters
- Width: 2.4in, height: 1.9in, depth: 1.8in, weight: 3.5oz

FEATURES

- CREE® LED technology – 50,000 + hours LED life
- High-brightness spotlight, low-brightness spotlight
- Focused spotlight beam for distance illumination
- Engineered polymer housing
- Single switch located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- Heavy-duty rubber strap for hard hat applications
- Waterproof and Dust proof
- Impact & chemical resistant
- Powered by 3 premium AAA alkaline batteries (included)

FL 1 STANDARD	HIGH	LOW
	60 LUMENS	40 LUMENS
	13h 30min	22h 45min
	80m	65m
	1615cd	1076cd
	2m	1m

SAFETY RATING

cETLus, ATEX and IECEx listed Intrinsically Safe and PESO approved

Patent 7,738,229

INCLUDED

- Headlamp
- 3 Premium alkaline AAA batteries
- Elastic non-slip head strap
- Heavy-duty rubber hard hat strap



Heavy-duty rubber head strap

XPP-5452G SPECIFICATIONS

- Lumens: high spotlight-115, low spotlight-65
- Run-time: high spotlight-4.5 hrs, low spotlight-13 hrs
- Beam distance: 92 meters
- Water Dust rating: IP-67
- Drop rating: 2 meters
- Width: 2.4in, height: 1.9in, depth: 1.8in, weight: 3.5oz

FL 1 STANDARD	HIGH	LOW
	115 LUMENS	65 LUMENS
	4h 30min	13h
	92m	67m
	2152cd	1141cd
	2m	1m

Model	UPC 0 17398
XPP-5450G	80300 7
XPP-5452G	80301 4

Clients



Nightstick 5450 Headlamp

ID 4001184
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T3 Ex ia IIC T3 Ga
CLASS II & III GRPS E-G T135C Intertek ITS 13 ATEX27854X
CLASS I ZONE 0 AEx ia IIC T3 Ga IECEx ETL 13.0031X
CLASS I ZONE 0 Ex ia IIC T3 Ga -20°C ≤ Tamb ≤ +40°C
⊕ II 1 G Ex ia IIC T3 Ga 1.5V/Cell AAA Alkaline
CE 0359

Conforms to:
ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11, ANSI/ISA 60079-26

Certified to:
CAN/CSA STD C22.2 No 157
CAN/CSA STD C22.2 No 60079-0
CAN/CSA STD C22.2 No 60079-11
CSA STD C22.2 No 25

Nightstick 5452 Headlamp

ID 4001184
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T3 Ex ia IIC T3 Ga
CLASS II & III GRPS E-G T135C Intertek ITS 13 ATEX27854X
CLASS I ZONE 0 AEx ia IIC T3 Ga IECEx ETL 13.0031X
CLASS I ZONE 0 Ex ia IIC T3 Ga -20°C ≤ Tamb ≤ +40°C
⊕ II 1 G Ex ia IIC T3 Ga 1.5V/Cell AAA Alkaline
CE 0359

Conforms to:
ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11, ANSI/ISA 60079-26

Certified to:
CAN/CSA STD C22.2 No 157
CAN/CSA STD C22.2 No 60079-0
CAN/CSA STD C22.2 No 60079-11
CSA STD C22.2 No 25