

Intrinsically Safe Multi-Function Dual-Light™ Angle Light

Rechargeable



The XPR-5572RA Rechargeable Intrinsically Safe Multi-Function Dual-Light™ Angle Light is a Flashlight, a Floodlight and Dual-Light Angle that is cULus, ATEX, and IECEx certified Intrinsically Safe and PESO Approved. The flashlight setting offers 3 user-selectable brightness setting of 200, 100 and 60 Lumens plus a strobe feature with a 267 meter beam distance. The ultra-tight beam is perfect for cutting through smoke and lighting up objects at great distances. The floodlight setting has 3 user-selectable brightness setting of 200, 100 and a "Survival Mode" of 20 lumens that provides just enough light in an emergency situation with a run-time of 3½ days. The Dual-light mode allows the user to simultaneously see objects at distance or through the smoke, as well as see the ground in front of them as they walk or work. The 5572 is powered by a rechargeable Lithium-ion battery pack. The 5572 meets requirements of NFPA-1971-8.6(2013).

INTRINSICALLY SAFE



TECHNOLOGY

200 Flashlight Lumens

200 Floodlight Lumens

200 Dual-Light™ Lumens



- cULus, ATEX, and IECEx certified Intrinsically Safe
- Flashlight/Floodlight/Dual-Light™
- User-selectable brightness settings on Flashlight & Floodlight including 20 Lumen Survival mode on Floodlight
- Meets the requirements for NFPA-1971-8.6 (2013)
- Charger meets requirements of NFPA-1901 (2009)
- PESO Approval No : A/P/HQ/DL/104/5544 (P409850)



XPR 5572RA

Intrinsically Safe Multi-Function Dual-Light™ Angle Light Rechargeable

FEATURES

- cULus, ATEX, and IECEx certified Intrinsically Safe
- CREE® LED technology – 50,000 + hours LED life
- Flashlight/Floodlight/Dual-Light™
- 3 User-selectable brightness settings on the flashlight plus a strobe
- High-efficiency deep parabolic reflector creating a sharp focused flashlight beam
- 3 User-selectable brightness setting on the floodlight including a 20 Lumen Survival Mode
- Dual-light (both the flashlight & floodlight on at the same time) provides for maximum lighting versatility and user safety
- Glass-filled Nylon Polymer housing
- Dual body switches
- Heavy-duty stainless-steel pocket clip
- Battery charge status indicator (for use only with rechargeable battery)
- Waterproof and Dust proof
- Impact & chemical resistant
- Light meets the requirements of NFPA-1971-8.6 (2013)
- Charger meets the requirements of NFPA-1901 (2009) mounted in any position
- Serialized for personal identification
- Powered by rechargeable Lithium-ion battery pack (included)
- Can also be powered by 6 AA batteries (not included) using the AA Battery Carrier (included)
- Limited Lifetime Warranty*

SPECIFICATIONS

- Lumens: flashlight high-200, medium-100, low-60, floodlight high-200, medium 100, survival 20, Dual-Light-200
- Run-time: flashlight high-6 hrs, medium-11 hrs 30 min, low- 22 hrs 30 min, floodlight high-6 hrs, medium-11 hrs 30 min, survival-30 hrs, Dual-Light-6 hrs
- Recharge time: 6 hours
- Beam distance: 267 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 7.6in, width: 3.2in, depth: 3in, bezel diameter: 2.8 in, weight: 13.7oz

FL 1 STANDARD	DUAL-LIGHT	HIGH	MEDIUM	LOW
	200 LUMENS	200 LUMENS	100 LUMENS	60 LUMENS
	8h	6h	11h	22h
	235m	267m	199m	145m
	13836cd	22249cd	14828cd	7790cd
	2m			
	1m			

INCLUDED

- Light
- Rechargeable Lithium-ion Battery Pack
- Wall or Vehicle Mounted Charger
- AA Battery Carrier (AA batteries not included)
- AC & DC Power Supplies



High-efficiency deep parabolic reflector

Wide-beam floodlight

Heavy-duty stainless-steel pocket clip

Wall or Vehicle Mounted Charger

Clients

Model	UPC 0 17398
XPR-5572R	80458 5



SAFETY RATING

Nightstick XPR-5572G/R
 Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
 UL listed for use with Bayco Li-Ion Battery Pack 5572-BATT or Primary 5570-BATT Battery Pack containing 6 AA Energizer Type EN91 or E91 batteries.

CLASS I DIV 1 GRPS A-D T4
 CLASS II & III DIV 1 GRPS E-G
 CLASS I ZONE 1 AEx ia IIC T4 Gb
 CLASS II ZONE 20 IIC
 Ex ia IIC T4 Gb
 Ex ia IIC T4 Gb

Ex ia IIC T4 Gb
 DEMKO 16ATEX1773
 IECEx UL 16.0115
 -20°C ≤ Tamb ≤ +40°C
 3.7V/Cell
 UL = 4.75V

Conforms to:
 ANSIIUL STD 913, ANSIIUL 60079-0,
 ANSIIUL 60079-11

Certified to:
 CAN/CSA STD C22.2 No 157
 CAN/CSA STD C22.2 No 60079-0
 CAN/CSA STD C22.2 No 60079-11

*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.