

Intrinsically Safe Dual-Light™ Headlamp w/Hard Hat Clip and Mount



TECHNOLOGY

160 Lumens
 Dual-Light™

115/60 Lumens
 Spotlight

120/60 Lumens
 Floodlight

Spot High

Spot Low



Flood High

Flood Low

Dual



- 160 Lumens in Dual-Light™ mode
- cETLus, ATEX, INMETRO and IECEx listed Intrinsically Safe
- Integrated Stainless Steel Clip attaches to hard hat mounting bracket (included)
- 5 modes: high/low spotlight, high/low floodlight & Dual-Light™
- IP-67 rated water / dust proof
- Powered by 3 AAA batteries (included)
- PESO Approval No : A/P/HQ/DL/104/5544 (P409850)

This 3 AAA Intrinsically Safe Dual-Light™ Headlamp w/Hard Hat Clip & Mount is cETLus, ATEX, INMETRO and IECEx listed Intrinsically Safe and PESO Approved. This headlamp features a multi-position tilt head design and includes an integrated Stainless Clip and adhesive hard hat mounting bracket for hands-free operation. The dual top mounted switches provide user-selectable high or low-brightness spotlight, high or low-brightness floodlight operation and our exclusive Dual-light design... the ability to turn on both the spotlight and the floodlight at the same time for maximum user safety and lighting versatility. Power comes from 3 AAA premium batteries (included).

INTRINSICALLY SAFE



XPP 5454GC



XPP-5454GC

Intrinsically Safe Dual-Light™ Headlamp

w/Hard Hat Clip and Mount



FEATURES

- cETLus, ATEX, INMETRO and IECEx listed Intrinsically Safe
- CREE® LED technology – 50,000 + hours LED life
- 5 modes: high/low spotlight, high/low floodlight & Dual-Light™
- Integrated Stainless Steel Clip attaches to hard hat mounting bracket (included)
- Focused spotlight beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-light (any spotlight & floodlight mode at same time) for maximum versatility
- Engineered polymer housing
- Dual switches located on top of light
- Adjustable ratchet tilt head
- Waterproof and Dust Proof
- Impact & chemical resistant
- Powered by 3 AAA batteries (included)

SAFETY RATING

cETLus, ATEX, INMETRO, and IECEx listed Intrinsically Safe.

Nightstick 5454 Headlamp

ID 4008947
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

Intertek

CLASS I DIV 1 GRPS A-D T3 Ex ia IIC T3 Ga
CLASS II & III GRPS E-G T135C Intertek ITS 13 ATEX27928X
CLASS I ZONE 0 AEx ia IIC T3 Ga IECEx ETL 13.0045X
CLASS I ZONE 0 Ex ia IIC T3 Ga -20°C ≤ Tamb ≤ +40°C
©II 1 G Ex ia IIC T3 Ga 1.5V/Cell AAA Alkaline

CE 0359

Conforms to: ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11, ANSI/ISA 60079-26

Certified to: CAN/CSA STD C22.2 No 157, CAN/CSA STD C22.2 No 60079-0, CAN/CSA STD C22.2 No 60079-11, CSA STD C22.2 No 25

Patent 7,738,229



Industrial strength PSA backing



Fits most hard hats



Integrated stainless steel clip



Tool-less secure pressure fit mounting

SPECIFICATIONS

- Lumens: high spotlight-115, low spotlight-60, high floodlight-120, low floodlight-60, dual-light-160
- Run-time: high spotlight-5 hrs, low spotlight-16.25 hrs, high floodlight-5.25 hrs, low floodlight-16.75 hrs, dual-light-3.5 hrs
- Beam distance: 94 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Width: 2.6in, length: 2.1in, depth: 1.8in, weight: 3.4oz

FL 1 STANDARD	DUAL-LIGHT	HIGH	LOW
	160 LUMENS	115 LUMENS	60 LUMENS
	3h 30min	5h	16h 15min
	94m	82m	60m
	1711cd	1668cd	882cd
	2m		
	1m		

INCLUDED

- Headlamp w/ Hard Hat Clip
- 3 Premium alkaline AAA batteries

Model UPC 0 17398

XPP-5454GC 80450 9

Clients

