



aska[®]

PORTABLE LIGHTING SOLUTIONS

Shapeshifter LED Light Tower

ASKA Shapeshifter LED Light
180°-360° is the latest addition to
the mobile LED light tower category.

BIS REGISTERED LED lamp and also IP 67 rated.



Manufactured by:
ASKA EQUIPMENTS PRIVATE LIMITED
(Formerly known as Aska Equipments Limited)
R-482, New Rajendra Nagar,
Acharya Sushil Muni Square,
Shankar Road, New Delhi -110060.
Landline : **011-49458.800** | Fax : **011-49458844**
Toll Free : **18001238611**
Website : **www.lighttower.in**

Shapeshifter LED Light Tower

Model Shapeshifter LED 180°- 360°

KEY FEATURES:

1. Deployed by a single person
2. Produces min 50000 lumens with 360-watt power consumption (60 watt x 6)
3. Can be used as 360° or 180° Flood Light
4. Produces about 30% more light than a 4x400W halogen system
5. Consumes 75% less power compared to a 4x400 halogen system
6. Multiple units can be transported in a regular car
7. Requires no prior training or certification and is simple to operate
8. Multiple units can be operated from a portable generator
9. Built for easy replacement of parts with a modular design
10. Can be used both indoors and outdoors (IP67) and is also suitable for extreme temperatures
11. Safe to operate with colour-coded guidance
12. Takes up little space when stored
13. 50000 hours life span on LED, 2-year warranty on structural components
14. 45 kg weight for complete system
15. Integrated wheels
16. Dimmable light
17. Adjustable LED angles
18. 13.5 feet height from the ground when extended
19. Pneumatic operation with one touch of a button for raising the mast
20. Adjustable leg angles
21. Genset or battery bank for power
22. LED lamp wattage 60 watt x 6 (360 watts)

Total lumen	More than 50,000
LED lamp with Dimmer	Yes
IP Rating for LED lamp/ Luminaire	IP 67
BIS approved LED lamp / Luminaire	YES
Operating temperature	-20 °C to +50 °C
Input voltage	100 to 305 VAC/ 50 Hz
Tower mast material	Lightweight aluminium alloy (special grade high strength)
Mast operation type	Pneumatic type with a press of a single button
Total height from ground	Minimum 4 meter
180° light to 360° operation	Yes possible
Integrated wheels	Yes
Adjusted tripod legs	Yes
Transport dimensions	510 mm x 495 mm x 1280 mm
Weight of the light tower	45 kg (without accessories)
Power source	Honda EP 1000 genset runs for 9 hours on full load
Wind resistance	Upto 12.5M/s without resistance
Certifications	BIS approved LED luminaire & drivers. In addition, the complete product was tested by NABL approved lab

Option of Supplies available

Only the Light Tower
without any power source

Light tower with
Honda EP 1000 Genset

Light tower with
Battery Bank



Lower Height



All light at one direction



Easy to move



Light Weight