



# **BENEFITS**



**PORTABLE** 

**DETACHABLE** 

**EASY TO CARRY** 

# **BUTTERFLY LITE**

Modular Lighting System with Remote Control

Lighting System for Temporary and Emergency Illumination Requirements.

S No.	TECHNICAL SPECIFICATIONS	
1.	Power:	600 W
2.	Number and power of the LEDs	4x150W
3.	Nominal lighting power (in Lumens output)	Minimum 67,000 lm
4.	LED life	50,000 hr
5.	Lux level at 1250 sqm ( approx)	12 Lux average
6.	Lux level at 7850 sqm (approx.)	1.5 Lux average
7.	Lux level at 11310 sqm (approx.)	1.0 Lux average
8.	Diffuser tube height:	Minimum 79 cm
9.	Lighting with 2-channel wireless remote switch with the following steps:	0/300/ 600W or 600/300/0W
10.	No. of remotes	2 pcs with minimum 30 meter range operation
11.	Total height from ground level including tripod and modular light (diffuser tube) ± 5%	4 meters
12.	Total height of modular light with open system:	100 cm ±5
13.	Height with closed system modular light:	23 cm ±5
14.	Total weight of complete modular light including diffuser tube (excluding accessories like Gen Set (EP 1000 750VA), 1 empty water bag with belt, packing box, 3 anchor grouting hooks, 3 ropes.	Less than 15 kg
15.	Total weight of complete light module with protection cap (excluding tripod - light supporting stand)	Less than 8.5 kgs
16.	Weight of light supporting tripod stand / base	Should be less than 6.5 kgs

# **ACCESSORIES**

### **Included Accessories**







3 no anchor grouting hooks weight



Carrying Case for tripod and LED light



1 Empty Water bag with belt



## **Optional Accessories**



Power Source Genset EP1000 (750VA)

R-482, New Rajendra Nagar, Acharya Sushil Muni Square, Shankar Road, New Delhi -110060

Tel.: +91-11-49458800 (30 lines) Fax: +91-11-49458844 Email: info@askagroup.com Website: www.askagroup.com

#### **Sales & Service Centers**